

# Solenoid Connectors and Cables



## Solenoid Connectors for Ceram™, Series 740, and CD07™ Valves (DIN 43650-FORM A/ISO 4400 30MM)

### STRAIN RELIEF CONNECTORS NON-LIGHTED



8941000302\*  
(Old Part No. H -894100-00302)  
(Standard)



\*\*Part No. R432013747  
(Old Part No. P -067325-00000)  
(for use with wireways)

### 1/2" CONDUIT CONNECTORS NON-LIGHTED




Part No. R432015626  
(Old Part No P -069390-00000)  
(Molded Engineering Plastic)



Part No. R432015781\*\*  
(Old Part No. P -069707-00000)  
(Metallic)

### Lighted




Part No.	Old Part No.	
**R432013726	P -067261-00000	120 VAC
**R432013728	P -067262-00000	240 VAC
**R432013729	P -067264-00000	12 VDC
**R432013730	P -067265-00000	24 VDC
**R432015629	P -069417-00000	24 VAC

### 3/8" CONDUIT CONNECTOR NON-LIGHTED



Part No. R432015404\*\*\*  
(Old Part No. P -068674-00000)

### Lighted



Part No.	Old Part No.	
R432008421	P -026078-00001	120VAC***
R432008422	P -026078-00002	240 VAC***
R432008423	P -026078-00004	12 VDC***
R432008424	P -026078-00005	24 VDC***
R432008425	P -026078-00006	24 VAC***

## Solenoid Connectors For Series 581 and Series 830 Valves ONLY (INDUSTRIAL FORM§ 22MM)

### Non-Lighted



\*8941004702  
Old Part No. H -894100-04702

### STRAIN RELIEF CONNECTORS

Part No.	Old Part No.	
*R432013878	P -067854-00000	120 VAC
*R432013879	P -067855-00000	240 VAC
*R432013880	P -067857-00000	12 VDC
*R432013881	P -067858-00000	24 VDC
*R432008426	P -026079-00000	24 VAC

### Lighted




§ Not FORM B.

## Solenoid Connectors for Series 840, Series 579, & Series TC Valves ONLY (Form C) 15MM

VOLTAGE (lighted version)	PART NO.	OLD PART NO.
120 VAC/DC (Without Lead)	R432011981	P -048824-00001
120 VAC/DC (W/3' LEAD)	R432011961	P -048803-00001
120 VAC/DC (W/6' LEAD)	R432011963	P -048804-00001
24 VAC/DC (Without Lead)	R432011982	P -048824-00005
24 VAC/DC (w/3' LEAD)	R432011962	P -048803-00005
24 VAC/DC (W/6' LEAD)	R432011964	P -048804-00005

### Solenoid Connector Lighted



### Strain Relief Solenoid Connector Non-Lighted



Part No.  
8941012202  
(Old part no.  
H -894101-02202)

Recommended Wire Size for Solenoid Connector: 18-22 gauge wire Cable diameter: .080" to .265" O.D.  
R432008830 (Old Part No. P -027609-00000) 1/2" conduit connector for 840 wireway.

\*0.236-0.315 O.D. Cable Diameter, \*\*0.315-0.394 O.D. Cable Diameter, \*\*\*Cable Diameter up to 0.200  
All connectors this page: Maximum Wire Size A.W.G. #14. (14 gauge may not fit in lighted connector.)