


Pneumatic connection technologies → Push-In fittings

Series QR1-S standard

► Y-plug connector, reducing, double ► push-in fitting ► Ø 6 - Ø 8 ► push-in fitting, 4x ► Ø 4 - Ø 6 ► QR1-S-RYD



Ambient temperature min./max.  
Working pressure min./max.

+0°C / +60°C  
-0.95 bar / 10 bar


Materials:  
Screw  
Housing  
Seal  
Tooth lock washer  
Release ring  
Release ring holder

nickel-plated  
Polybutyleneterephthalate  
Acrylonitrile Butadiene Rubber  
Stainless steel  
Polyoxymethylene  
Die cast zinc; Brass, nickel-plated

Technical Remarks

- The series QR1 (plastic) and QR2 (metal) can not be combined
- For further information about assembling and tolerances of adaptable tubing, see the section "Technical information".

Dimensions



00117295

Part No.	Port G	Port D	Ø dx	A	B	F	J	Ø P1	Ø P2	Delivery quantity [Piece]	Weight [kg]
<b>R412005344</b>	Ø 6	Ø 4	3.2	37.2	17	14.2	10.4	13	10.4	10	0.0128
<b>R412005345</b>	Ø 8	Ø 6	3.5	40.6	18.5	16.9	13	14.4	13	10	0.0175