



XD Series Electronic Meters

Dependable and Easy-to-Use Fluid Dispense Meters



Accurate dispensing for a wide variety of vehicle or machine service applications

- Durable, sealed-electronic design ideal for dispensing petroleum- and synthetic-based oils in extreme environmental conditions
- Screw-tight nozzle for positive shut off
- Ball bearing swivel for ease of use
- Reset capable for periodic dispense history information
- 7-year warranty

PROVEN QUALITY. LEADING TECHNOLOGY.



Quality You Can Depend On

More Uptime to Increase Your Bottom Line

Graco dispense meters are engineered for professionals with quality materials that last. Each model has been rigorously tested to ensure the highest performance for your demanding applications, so you can be sure it will work when you need it.

ELECTRONIC METERS

Designed for dispensing petroleum- and synthetic-based oils in high-volume applications including mining operations, heavy construction, and industrial plants

XDM6 Electronic Meter

Maximum Flow 22.7 lpm (6 gpm)
 Minimum Flow..... 0.46 lpm (0.12 gpm)
 Maximum Operating Pressure..... 103 bar (1.500 psi)
 Units of Measure quarts, pints, gallons, liters
 Operating Temp Range -20 - 55° C (-4 - 130° F)
 Accuracy/Repeatability..... +/- 0.6%
 Warranty 7 years

XDM12 Electronic Meter

Maximum Flow 45.4 lpm (12 gpm)
 Minimum Flow..... 0.46 lpm (0.12 gpm)
 Maximum Operating Pressure..... 103 bar (1.500 psi)
 Units of Measure quarts, pints, gallons, liters
 Operating Temp Range -20 - 55° C (-4 - 130° F)
 Accuracy/Repeatability..... +/- 0.6%
 Warranty 7 years



XDI12 Inline Meter

Maximum Flow 45.4 lpm (12 gpm)
 Minimum Flow..... 0.46 lpm (0.12 gpm)
 Maximum Operating Pressure..... 103 bar (1.500 psi)
 Units of Measure quarts, pints, gallons, liters
 Operating Temp Range -20 - 55° C (-4 - 130° F)
 Warranty 7 years

Improved meter interface features a long-lasting, replaceable lithium battery



GRACO BVBA Industrieterrein Oude Bunders
 Slakweidestraat 31 • B-3630 Maasmechelen
 Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777
 www.graco.com

©2015 Graco BVBA 352401ENEU Rev. A 01/16
 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.



All-Weather Protection

Sealed electronics for use in extreme environmental conditions

Improved Interface

Upgraded interface featuring a long-lasting, replaceable lithium battery

Impact-resistant shroud

Resists scratches and protects knob and dial from damage

Ergonomic Handle Design

Comfortable, secure grip for any application

High Flow Rate

Industry-leading 45.4 l/mn flow rate capability

Common connection point

Makes installation quick and easy

Ordering Information

XDM6 Electronic Meters

		Rigid Extension	Flexible Extension	Gear Lube Extension
NPT	1/2" inlet	24V545	24V548	24V547
BSPP		24Y238	24Y242	24Y239
BSPT		24Y249	24Y251	24Y250

XDM12 Electronic Meters

		Rigid Extension	Flexible Extension
NPT	3/4" inlet	24V549	24V550
	1/2" inlet	24V551	24V552
BSPP	3/4" inlet	24Y243	24Y244
	1/2" inlet	24Y246	24Y248
BSPT	3/4" inlet	24Y252	24Y253
	1/2" inlet	24Y254	24Y255

XDI12 In-Line Meters

24V553	XDI12 Meter
24V554	Replacement electronics