



LD Enclosed Hose Reels

Hose Reels with Flexible Mounting Options



Simple to install—mounts in minutes!

- Enclosed reel for safety and protection—compact enclosure extends hose life
- Full flow swivel—maximizes fluid output while minimizing pressure loss
- Easily add or decrease spring tension while pressurized

PROVEN QUALITY. LEADING TECHNOLOGY.



Quality hose reels mount in minutes—gives you years of worry-free performance!



Ceiling/Wall Swivel Mount (standard)



Ceiling/Wall Stationary Mount (optional)



Bench Mount (optional)

Contact us today!

To receive product information or to speak with a Graco representative, call 800-533-9655 or visit us online at www.graco.com.

©2009 Graco Inc. Form No. 340432 Rev. A 12/09 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Economical hose reel gets you up and running—fast!



Reduce clutter and increase workplace safety with a Graco one piece hose reel. Designed for dealerships, service garages, collision repair and industrial manufacturing facilities. Quickly mounts to wall, ceiling, bench, tanks or in cabinets. Complete packages available with LD oil meters and hose inlet kit to get you up and running fast!

ORDERING INFORMATION*

Application	Model	Hose Inlet Kit (BSPT)	Hose Inlet Kit (NPT)**
Air Only	HEL13D	24C437	24C443
	HEL15D	24C437	24C443
Air/Water	HEL23D	24C438	24C444
	HEL25D	24C438	24C444
	HEL33D	24C438	24C445
	HEL34D	24C438	24C445
Petroleum- and Synthetic-based Oils	HEM23D	24C440	24C537
	HEM33D	24C440	24C538
Grease	HEH13D	24C442	24C539

*Inlet kits ordered separately

**Includes two fittings to convert BSPT(m) to NPT(m)

OIL DISPENSING PACKAGES (Reel, Meter, Inlet Hose)


Package number	LD Reel	Hose Inlet Kit	Valve/Meter
24D197	HEM33D	24C538	256215, LDM5 Rigid with trigger guard
24D198	HEM33D	24C538	255751, LDM5 Flex without trigger guard
24D199	HEM33D	24C538	256216, LDP5 Rigid with trigger guard
24D200	HEM33D	24C538	255277, LDP5 Flex without trigger guard

ACCESSORIES

Includes all parts to bench-, table- or tank top-mount reel on wall or ceiling

Part Number	Mounting Options
24C772	Tote, Bench or Wall Mount Post

Tote, Bench or Wall Mount Post
24C772



TECHNICAL SPECIFICATIONS

Application	Model	Pressure psi (bar)	Hose ID x Length	Inlet (bspt)	Outlet (bspt)	Operating Temp.
Air Only	HEL13D	250 (17.2)	6 mm x 11 m (1/4 in x 35 ft)	1/2 in	1/4 in	-14–140 °F (-10–60 °C)
	HEL15D	250 (17.2)	6 mm x 15 m (1/4 in x 50 ft)	1/2 in	1/4 in	
Air/Water	HEL23D	250 (17.2)	10 mm x 11 m (3/8 in x 35 ft)	1/2 in	3/8 in	-0–140 °F (-17–60 °C)
	HEL25D	250 (17.2)	10 mm x 15 m (3/8 in x 50 ft)	1/2 in	3/8 in	
	HEL33D	250 (17.2)	12 mm x 11 m (1/2 in x 35 ft)	1/2 in	1/2 in	
	HEL34D	250 (17.2)	12 mm x 14 m (1/2 in x 45 ft)	1/2 in	1/2 in	
Petroleum/Synthetic-based Oils	HEM23D	1800 (124)	10 mm x 11 m (3/8 in x 35 ft)	1/2 in	3/8 in	
	HEM33D	1800 (124)	12 mm x 11 m (1/2 in x 35 ft)	1/2 in	1/2 in	
Grease	HEH13D	5000 (345)	6 mm x 11 m (1/4 in x 35 ft)	3/8 in	1/4 in	

Instruction Manual=313938