MITSUBISHI

FX3U-32BL Battery MODEL CODE: 09S312

STARTUP AND MAINTENANCE PRECAUTIONS

DANGER

- Use the battery for memory backup correctly in conformance to the manual of each product.
- Use the battery for memory backup correctly in conformance to the manual of each product.

 Use the battery only for the specified purpose.

 Connect the battery correctly.

 Do not charge, disassemble, heat, put in fire, short-circuit, connect reversely, weld, swallow or burn up the battery, or apply excessive forces (vibration, impact, drop, etc.) on the battery, or apply excessive forces (vibration, impact, drop, etc.) on the battery, or apply excessive forces to direct sunlight.

 Do not store or use the battery in a place at high temperature or exposed to direct sunlight.

 Do not expose to water, bring near fire or touch the contents such as liquil elakage directly.

 Incorrect handling of the battery may cause heat generation, burst, ignition, liquid leakage or deformation, and lead to injury, fire or failures and malfunctions of facilities and other equipment.

 Power off the Devices with Built-in Batteries (all phase) before attaching/detaching the battery.

 Failure to do so may cause electric shock or damage to the product.

 Please contact a certified electronic waste disposal company for the environmentally safe recycling and disposal of your device.

1. Specification

Product name	Nominal voltage
FX3U-32BL	3V

2. Battery Replacement

For the replacement procedure, refer to respective Devices with Built-in Batteries refer to the User's Manual of the

July 2011 JY997D14101D






原产地 日本国 合格证 MITSUBISHI ELECTRIC CORPORATION Made in Japan

3. Battery Life and Date of Manufacture

- Battery Life and Date of Manufacture
 Battery life: Approx. 5 years, when IU2-3M10(L) or IU2-1EMES is used, it is about 3 years. (ambient temperature: 25°C)
 Replacement period: Within 4 or 5 years, when IU2-3M10(L) or IU2-1EMES is used, it is about 2 years.
 (Due to natural discharge within all batteries, please prepare a replacement before the above-stated replacement period.)
- Example of date-of-manufacture indication:



 ∇

4. Precautions for Battery Transportation
When transporting lithium batteries, follow the transportation regulations.

Product name	Battery type	Product supply status	Lithium Content (gram/unit)	Mass*1 (gram/unit)
FX3U-32BL	lithium metal battery	Cell	0.15	30

*1 The value indicates the mass with packaging.

Comply with IATA Dangerous Goods Regulations, IMDG code and the local transport regulations when transporting products listed above

Also, consult with the shipping carrier.

5. Handling of Batteries in EU Member States

for battery EU

*1 This symbol to the left is for EU member states

The symbol is specified in the new EU Battery Directive (2006/66/EC) Article 20 "Information for end-users" and Annex II.

- The symbol to the above indicates that batteries need to be disposed of separately from other wastes.
- The new EU Battery Directive (2006/66/EC) requires the following when marketing or exporting batteries and/or devices with built-in batteries to EU member states.
 - To print the symbol on batteries, devices, or their packaging
 - ol in the r

- To explain the symbol in the mandals of the products		
Product name	Battery type	
FX3U-32BL	Lithium Manganese Dioxide Battery	