Futbols



50FA1 SERIES

- Bolt to the process side of a flange-flange manifold to allow connection of process flange taps or process root valves
- Allow flanges to be connected to threaded process piping while maintaining the ease of removal or repair of the manifold if maintenance is required
- Provide a 1/16" offset connection from the bolt holes to give connection centers of 2", 2-1/8" or 2-1/4"
- Kit Includes: (2) Futbols, (4) hex bolts 7/16"-20, (2) PTFE face seals

SPECIFICATIONS		
Materials	Zinc-Nickel plated Carbon Steel, 316 Stainless Steel*	
Connection	1/2" NPT	
Weight	Approximately 2.1 lb.	

^{*} All 316SS products meet the requirements of NACE MR0175/ISO 15156-3.

For NOSHOK Steel Futbols:



WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For NOSHOK Stainless Steel Futbols:



WARNING: This product can expose you to chemicals including Chromium (VI) and Nickel, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



ORDERING INFORMATION			
SERIES	50FA1 Futbol		
MATERIALS	CS Steel	SS 316 Stainless Steel	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.



Futbols

Front View Side View



