


R4OMLO

Run Tee – BSPP
 (for ISO 1179-1 Port)
 ORFS / BSPP-ORR / ORFS




* Y – Across
Wrench Flats

TUBE FITTING PART #	END SIZE			M (mm)	N (mm)	Y (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1 & 3		2				S	-SS
	(mm)	(in.)	BSPP					
4R4OMLO	6	1/4	1/8 - 28	21.5	30	14	4.0	
4-4-4R4OMLO	6	1/4	1/4 - 19	23.5	36	19	4.0	
6R4OMLO	8,10	3/8	1/4 - 19	25	36	19	4.0	
6-6-6R4OMLO	8,10	3/8	3/8 - 19	26.5	38	19	4.0	
8R4OMLO	12	1/2	3/8 - 19	28	38	19	4.0	
8-8-8R4OMLO	12	1/2	1/2 - 14	31	48.5	27	4.0	
10R4OMLO	14,15,16	5/8	1/2 - 14	33.5	48.5	27	4.0	
10-12-10R4OMLO	14,15,16	5/8	3/4 - 14	36	51.5	30	4.0	
12R4OMLO	18,20	3/4	3/4 - 14	37.5	51.5	30	4.0	
12-16-12R4OMLO	18,20	3/4	1 - 11	41	58.5	37	4.0	
16R4OMLO	22,25	1	1 - 11	41.5	58.5	37	4.0	

KLO

Union Cross
 ORFS (all four ends)

SAE 520501




* JJ – Across
Wrench Flats

TUBE FITTING PART #	END SIZE		M (in.)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1-4 (in.)	JJ (in.)		-S	-SS
	4 KLO	1/4			
6 KLO	3/8	3/4	0.98	9.2	
8 KLO	1/2	3/4	1.10	9.2	
10 KLO	5/8	1 1/16	1.31	6.0	
12 KLO	3/4	1 3/16	1.47	6.0	
16 KLO	1	1 7/16	1.64	6.0	
20 KLO	1 1/4	1 5/8	1.76	5.0	

KMLO

Union Cross – mm Hex
 ORFS (all four ends)

ISO 8434-3 K
 SAE 52M0501



TUBE FITTING PART #	END SIZE		L7 (mm)	S2 (mm)	STANDARD Dynamic Pressure (x 1,000 PSI)	
	1-4				S	SS
	(mm)	(in.)				
4KMLO	6	1/4	21.5	14		
6KMLO	8,10	3/8	25	19		
8KMLO	12	1/2	28	19	9.2	
10KMLO	14,15,16	5/8	33.5	27		
12KMLO	18,20	3/4	37.5	30		
16KMLO	22,25	1	41.5	36		
20KMLO	28,30,32	1 1/4	44.5	41		
24KMLO	35,38	1 1/2	49	50		

Dimensions and pressures for reference only, subject to change.