


FIXOCAP F

Order No.: 1201471

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1201471>

Rail adapter, snaps into NS 32 DIN rail, plastic with embedded M4 and M6 nuts, for attaching switchgear

Commercial data

| | |
|--------------------------|--|
| GTIN (EAN) |  |
| sales group | B224 |
| Pack | 100 pcs. |
| Customs tariff | 85369010 |
| Catalog page information | Page 386 (CL-2002) |

Product notes

WEEE/RoHS-compliant since:
01/01/2003



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

| | |
|---------------------------------|------------------|
| Color | white |
| Base element material | Polyacetate |
| Ambient temperature (operation) | -20 °C ... 80 °C |

Accessories

| Item | Designation | Description |
|-----------------|-------------------------------|---|
| Assembly | | |
| 1201028 | NS 32 AL UNPERF 2000MM | G rail 32 mm (NS 32) |
| 1201280 | NS 32 CU/120QMM UNPERF 2000MM | G-profile DIN rail, deep-drawn, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m |
| 1201358 | NS 32 CU/35QMM UNPERF 2000MM | G-profile DIN rail, material: Copper, unperforated, height 15 mm, width 32 mm, length 2 m |
| 1201002 | NS 32 PERF 2000MM | G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m |
| 1201015 | NS 32 UNPERF 2000MM | G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m |

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;