


SACB-12X0,5/ 3X1,0-50,0 PUR

Order No.: 1503360

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1503360>

Master cable for sensor/actuator boxes, with PE conductor,
unshielded, material PUR/PVC, 15-pos., 12 x 0.50 mm² and 3 x 1.00
mm², length: 50 m

Commercial data	
GTIN (EAN)	
Note	Made-to-order
sales group	D192
Pack	1 pcs.
Customs tariff	85366990
Catalog page information	Page 200 (PC-2011)

Product notes

WEEE/RoHS-compliant since:
02/02/2006



[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Technical data	
General data	
Rated voltage	300 V
Master cable data	
Length of cable	50 m

Cable type	Master cable suitable for flexible cable conduit
Signal line cross section	12x 0.5 mm ²
AWG signal line	20
Conductor structure signal line	64x 0.10 mm
Power supply cross section	3x 1 mm ²
AWG power supply	17
Conductor structure, voltage supply	128x 0.10 mm
External diameter	10.5 mm
Max. bending cycles	1500000
Bending radius	105 mm
Traversing path	2 m
Traversing rate	2 m/s
Ambient temperature (operation)	-40 °C ... 90 °C (for fixed installation)
	-5 °C ... 80 °C (for flexible installation)

Accessories

Item	Designation	Description
Tools		
1212156	WIREFOX 4	Stripping tool, for lines and conductors (special for rubber and silicon insulations) of 0.1 - 4 mm ² , self-adjusting, stripping length up to 18 mm, cutting capacity up to 10 mm ² stranded / 1.5 mm ² solid
1212162	WIREFOX-D 13	Stripping tool, for stripping installation lines of Ø 8 - 13 mm , e.g. NYM 3 x 1.5 mm ² to 5 x 2.5 mm ² , single line stripping 0.2 mm ² - 4 mm ² , with longitudinal cut blade and sliding knife
1212161	WIREFOX-D 40	Stripping tool , for stripping cables of 4.5 mm - 40 mm-Ø, insulation thickness of up to 4.5 mm, pivoting blade for round, lengthwise, and spiral cuts

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;