


**SACB-16X0,34/2X0,75-50 PUR**

Order No.: 1539350

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1539350>

Master cable for sensor/actuator boxes, without PE conductor,  
unshielded, material PUR/PVC, 18-pos., 16 x 0.34 mm<sup>2</sup> and 2 x 0.75  
mm<sup>2</sup>, length: 50 m

Commercial data	
GTIN (EAN)	 4 046356 077767
Note	Made-to-order
sales group	D101
Pack	1 pcs.
Customs tariff	85444995
Catalog page information	Page 200 (PC-2011)

## Product notes

WEEE/RoHS-compliant since:  
06/21/2006



[http://  
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)  
Please note that the data given  
here has been taken from the  
online catalog. For comprehensive  
information and data, please refer  
to the user documentation. The  
General Terms and Conditions of  
Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Rated voltage	300 V
<b>Master cable data</b>	
Length of cable	50 m

Cable type	Master cable suitable for flexible cable conduit
Signal line cross section	16x 0.34 mm <sup>2</sup>
AWG signal line	22
Conductor structure signal line	42x 0.10 mm
Power supply cross section	2x 0.75 mm <sup>2</sup>
AWG power supply	19
Conductor structure, voltage supply	96x 0.10 mm
External diameter	10.1 mm
Max. bending cycles	1500000
Bending radius	105 mm
Traversing path	2 m
Traversing rate	2 m/s
Ambient temperature (operation)	-40 °C ... 80 °C (for fixed installation)
	-5 °C ... 80 °C (for flexible installation)

#### Accessories

Item	Designation	Description
<b>Tools</b>		
1212156	WIREFOX 4	Stripping tool, for lines and conductors (special for rubber and silicon insulations) of 0.1 - 4 mm <sup>2</sup> , self-adjusting, stripping length up to 18 mm, cutting capacity up to 10 mm <sup>2</sup> stranded / 1.5 mm <sup>2</sup> solid
1212162	WIREFOX-D 13	Stripping tool, for stripping installation lines of Ø 8 - 13 mm , e.g. NYM 3 x 1.5 mm <sup>2</sup> to 5 x 2.5 mm <sup>2</sup> , single line stripping 0.2 mm <sup>2</sup> - 4 mm <sup>2</sup> , with longitudinal cut blade and sliding knife
1212161	WIREFOX-D 40	<b>Stripping tool</b> , for stripping cables of 4.5 mm - 40 mm-Ø, insulation thickness of up to 4.5 mm, pivoting blade for round, lengthwise, and spiral cuts

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;