


**SAC-8P-100,0-PVC/SH-0,25**

Order No.: 1550708

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1550708>

Cable ring, PVC, black, 8-pos. shielded, conductor colors: White / brown / green / yellow / gray / pink / blue / red, cable length: 100 m

Commercial data	
GTIN (EAN)	 4 046356 170512
Note	Made-to-order
sales group	D117
Pack	1 pcs.
Customs tariff	85444995
Catalog page information	Page 198 (PC-2011)

## Product notes

WEEE/RoHS-compliant since:  
11/10/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Number of positions	8
Length of cable	100 m
<b>Conductor data</b>	
Cable type	PVC shielded black

Cable abbreviation	LiYF-C-Y
Conductor cross section	0.25 mm <sup>2</sup>
	0.227 mm <sup>2</sup> (Drain wire)
AWG signal line	24
Conductor structure signal line	32 x 0.10 mm
Core diameter including insulation	1.2 mm ±0.02 mm
Thickness, insulation	≥ 0.23 mm (Core insulation)
	≥ (Outer cable sheath)
External cable diameter	6.10 mm
Wire colors	Brown, white, green, yellow, gray, pink, blue, red
External sheath, color	Black RAL 9005
Insulation resistance	≥ 1 GΩ*km
Conductor resistance	≤ 78 Ω/km
Nominal voltage, conductor	300 V
Test voltage, conductor	2500 V
Overall twist	8 wires around filler to the core
Shielding	Braided copper wires
Optical shield covering	85 %
Outer sheath, material	PVC
Material, filler	PVC
Material conductor insulation	PVC
Conductor material	Bare Cu litz wires
Cable weight	64 kg/km
Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 80 °C (cable, flexible installation)

#### Certificates / Approvals



Certification

CUL Listed, UL Listed

**Accessories**

Item	Designation	Description
------	-------------	-------------

**Tools**

1212623	WIREFOX SAC	Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length
---------	-------------	--

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;