


## VS-25-ST-DSUB-3P-10S-LH

Order No.: 1655425

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655425>

D-SUB contact insert, shell size 3, with 10 signal contacts, for PCB assembly, angled, accommodation for 3 combined contacts, contact type pin, fixing with M3 thread and solder pins, for panel mounting frame VS-25-...

### Commercial data

GTIN (EAN)	
sales group	D501
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 437 (PC-2011)

### Product notes

WEEE/RoHS-compliant since:  
03/01/2005



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### Mechanical characteristics

Number of positions	9
Insertion/withdrawal cycles	≥ 50
External cable diameter	6 mm
Cable exit	Straight
Length of cable	2 m
Ambient temperature (operation)	0 °C ... 70 °C

**Material data**

Housing material	PVC
Contact material	Copper alloy
Contact surface material	Gold-plated
Outer sheath, material	PVC
Degree of protection	IP20

**Electrical characteristics**

Rated voltage (III/3)	125 V
Rated current	1 A

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;