


**PTSA 1,5/ 3-3,5-ZI MIX NZ236**

Order No.: 1711569

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1711569>

PC terminal block, Nominal current: 2 A, Nom. voltage: 250 V, Pitch:  
3.5 mm, Number of positions: 3, Connection method: Spring-cage  
conn., Mounting: Soldering, Conductor/PCB connection direction: 45 °

**Commercial data**

GTIN (EAN)	 4 046356 138147
Note	Made-to-order
sales group	E411
Pack	250 pcs.
Customs tariff	85369010

**Product notes**WEEE/RoHS-compliant since:  
05/03/2006

[http://  
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)  
Please note that the data given  
here has been taken from the  
online catalog. For comprehensive  
information and data, please refer  
to the user documentation. The  
General Terms and Conditions of  
Use apply to Internet downloads.

**Certificates / Approvals**

Certification

CUL, UL, VDE-PZI

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;