


PTSA 1,5/ 4-3,5-F RD WH NZ09

Order No.: 1713088

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1713088>

PC terminal block, Nominal current: 2 A, Nom. voltage: 250 V, Pitch:
3.5 mm, Number of positions: 4, Connection method: Spring-cage
conn., Mounting: Soldering, Conductor/PCB connection direction: 45 °

Commercial data

GTIN (EAN)	 4 046356 088800
Note	Made-to-order
sales group	E411
Pack	250 pcs.
Customs tariff	85369010

Product notesWEEE/RoHS-compliant since:
08/10/2005

[http://
www.download.phoenixcontact.com](http://www.download.phoenixcontact.com)
Please note that the data given
here has been taken from the
online catalog. For comprehensive
information and data, please refer
to the user documentation. The
General Terms and Conditions of
Use apply to Internet downloads.

Certificates / Approvals

Certification

CCA, CUL, UL, VDE-PZI

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;