


SMKDS 2,5/ 8-5,08

Order No.: 1736845

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1736845>

PC terminal block, Nominal current: 20 A, Nom. voltage: 400 V,
Pitch: 5.08 mm, Number of positions: 8, Connection method: Screw
connection, Mounting: Soldering, Conductor/PCB connection direction:
40 °

Commercial data

GTIN (EAN)	 4 046356 181976
Note	Made-to-order
sales group	E017
Pack	50 pcs.
Customs tariff	85369010
Catalog page information	Page 95 (CC-2011)

Product notesWEEE/RoHS-compliant since:
01/11/2007

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

CB, CCA, CSA, CUL, GOST, SEV, UL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;