

FLK 14/EZ-DR/ 450/KONFEK

Order No.: 2290847


The illustration shows a 50-pos. version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290847>

Round cable set, with two 14-pos. socket strips (1:1 connection), for connecting 8 channels, cable length: 4,5 m

Commercial data

| | |
|--------------------------|---|
| GTIN (EAN) |  4 017918 058203 |
| sales group | I680 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 282 (IF-2011) |

Product notes

WEEE/RoHS-compliant since:
05/02/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

| | |
|---|------------------|
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. current carrying capacity per path | 1 A |
| Max. conductor resistance | 0.16 Ω /m |
| Ambient temperature (operation) | -20 °C ... 50 °C |

| | |
|---|---|
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Connector | Flat-ribbon cable strip (IEC 60603-1) |
| Number of positions | 14 |
| Number of positions, control side | 14 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 14 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 4.5 m |
| Single wire, cross section | 0.14 mm ² |
| AWG | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| External diameter | 6.4 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding | no |

Certificates / Approvals



Certification

CUL, GOST, UL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;