

# FLK 40/EZ-DR/ 300/SLC


Order No.: 2294652

The illustration shows version FLK 40/EZ-DR/200/SLC



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2294652>

Round cable sets, with 40-pos. socket strips in fixed lengths (50-cm steps) to connect to 32-channel I/O cards of the SLC 500, length 3 m

Commercial data	
GTIN (EAN)	 4 017918 149024
sales group	I680
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 212 (IF-2011)

### Product notes

WEEE/RoHS-compliant since:  
10/01/2005



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General

Nominal voltage $U_N$	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A
Max. conductor resistance	0.16 $\Omega$ /m

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Number of positions	40
Number of positions, control side	40
Number of connectors, control side	1
Number of positions, module side	40
Number of connectors, modul side	1
Fixed cable length	3 m
Single wire, cross section	0.14 mm <sup>2</sup>
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
Test voltage	500 V AC (50 Hz, 1 min.)
External diameter	10 mm
Cable, preassembly	Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding	no
Standards/regulations	DIN EN 60352-4
	IEC 352-4

#### Certificates / Approvals



Certification

GOST

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;