

# FLK 50/4X14/EZ-DR/ 800/KONFEK


Order No.: 2296757



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2296757>

Round cable set, for connection to the VARIOFACE system cabling, with a 50-position socket strip and four 14-position socket strips, for splitting max. 32 channels into 4 x 8 channels, no. of positions: 50/ 4 x 14, cable length 8.0 m

## Commercial data

|                          |  |
|--------------------------|--|
| GTIN (EAN)               | <br>4 017918 593704 |
| sales group              | I680   |
| Pack                     | 1 pcs.   |
| Customs tariff           | 85444290   |
| Catalog page information | Page 286 (IF-2011)   |

## Product notes

WEEE/RoHS-compliant since:  
05/02/2005



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General

|   |           |
|---|-----------|
| Nominal voltage $U_N$                   | < 50 V AC |
|   | 60 V DC   |
| Max. current carrying capacity per path | 1 A       |

|   |   |
|---|---|
| Max. conductor resistance                     | 0.16 Ω/m  |
| Ambient temperature (operation)               | -20 °C ... 50 °C                                    |
| Ambient temperature (storage/transport)       | -20 °C ... 70 °C                                    |
| Number of positions, control side             | 50  |
| Number of connectors, control side            | 1   |
| Number of positions, module side              | 14  |
| Number of connectors, modul side              | 4   |
| Fixed cable length                            | 8 m   |
| Single wire, cross section                    | 0.14 mm <sup>2</sup>                                |
| AWG   | 26  |
| Conductor construction: Number of litz wires: | 7   |
| Single wire, material                         | Cu tin-plated                                       |
| External diameter                             | 6.3 mm  |
| Cable, preassembly                            | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding                                     | no  |

#### Certificates / Approvals



Certification

CUL, GOST, UL

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;