

FLK 14/EZ-DR/ 60/KONFEK/S


Order No.: 2299068

The illustration shows a 50-pos. version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2299068>

Round shielded cable set, with two 14-pos. female connectors, cable length: 0.6 m

Commercial data	
GTIN (EAN)	 4 017918 828196
Note	Made-to-order
sales group	I680
Pack	1 pcs.
Customs tariff	85444993

Product notes

WEEE/RoHS-compliant since:
08/09/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General	
Nominal voltage U_N	< 50 V AC
	60 V DC
Max. conductor resistance	0.16 Ω /m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Number of connectors, control side	1
Number of connectors, modul side	1
Shielding	no
	Tinned copper-braided shield, approx. 85% covering

Certificates / Approvals

Certifications applied for: UL / CUL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;