

FLK 34/EZ-DR/ 200/KONFEK


Order No.: 2299505

The illustration shows a 20-position version

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2299505>

Round cable set, with two 34-pos. socket strips (1:1 connection), cable length: 2 m

Commercial data

| | |
|--------------------------|---|
| GTIN (EAN) |  4 017918 886226 |
| sales group | I680 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 284 (IF-2011) |

Product notesWEEE/RoHS-compliant since:
01/01/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General**

| | |
|---|------------------|
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. current carrying capacity per path | 1 A |
| Max. conductor resistance | 0.16 Ω /m |
| Ambient temperature (operation) | -20 °C ... 50 °C |

| | |
|---|---|
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Connector | Flat-ribbon cable strip (IEC 60603-1) |
| Number of positions | 34 |
| Number of positions, control side | 34 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 34 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 2 m |
| Single wire, cross section | 0.14 mm ² |
| AWG | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| External diameter | 10 mm |
| Cable, preassembly | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding | no |

Certificates / Approvals



Certification GOST
Certifications applied for: UL / CUL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;