

CABLE-D 9SUB/B/S/150/KONFEK/S

Order No.: 2300009


The illustration shows a 15-position version



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2300009>

Round shielded cable set, with 9-pos. D-SUB female and male connectors, cable length: 1.5 m

Commercial data

| | |
|--------------------------|---|
| GTIN (EAN) |  4 017918 892968 |
| sales group | I682 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 290 (IF-2011) |

Product notes

WEEE/RoHS-compliant since:
05/22/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

| | |
|---|----------------------|
| Nominal voltage U_N | 125 V AC/DC |
| Max. current carrying capacity per path | 2 A |
| Max. conductor resistance | $\leq 0.09 \Omega/m$ |
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

| | |
|------------------------------------|--|
| Connector | D-SUB (IEC 60807-2/DIN 41652) |
| Number of positions | 9 |
| Plug connector, control side | D-SUB connector (IEC 60807-2/DIN 41652) |
| Number of positions, control side | 9 |
| Number of connectors, control side | 1 |
| Plug connector, module side | D-SUB socket (IEC 60807-2/DIN 41652) |
| Number of positions, module side | 9 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 1.5 m |
| Single wire, cross section | 0.25 mm ² |
| AWG | 24 |
| External diameter | 7.5 mm |
| Shielding | Tinned copper-braided shield, approx. 85% covering |
| Insertion/withdrawal cycles | > 200 |

Certificates / Approvals



Certification

CUL, GOST, UL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;