


# CABLE-D37SUB/B/S/150/KONFEK/S

Order No.: 2302214

The illustration shows a 15-position version

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2302214>Round shielded cable set, with 37-pos. D-SUB female and male  
connectors, cable length: 1.5 m

## Commercial data

GTIN (EAN)	
sales group	I682
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 290 (IF-2011)

## Product notes

WEEE/RoHS-compliant since:  
05/22/2006

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General

Nominal voltage $U_N$	125 V AC/DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	$\leq 0.09 \Omega/m$
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Connector	D-SUB (IEC 60807-2/DIN 41652)
Number of positions	37
Plug connector, control side	D-SUB connector (IEC 60807-2/DIN 41652)
Number of positions, control side	37
Number of connectors, control side	1
Plug connector, module side	D-SUB socket (IEC 60807-2/DIN 41652)
Number of positions, module side	37
Number of connectors, modul side	1
Fixed cable length	1.5 m
Single wire, cross section	0.25 mm <sup>2</sup>
AWG	24
External diameter	12.5 mm
Shielding	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

#### Certificates / Approvals



Certification

CUL, GOST, UL

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;