

CABLE-D25SUB/S/S/100/KONFEK/S

Order No.: 2305635

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2305635>

Assembled, shielded circular cable, with D-SUB pin strip, 25-pos. from both sides, cable length: 1m

Commercial data

GTIN (EAN)	 4 046356 011976
Note	Made-to-order
sales group	I682
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 291 (IF-2011)

Product notes

WEEE/RoHS-compliant since:
05/22/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General**

Nominal voltage U_N	125 V AC/DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	$\leq 0.09 \Omega/m$
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Connector	D-SUB (IEC 60807-2/DIN 41652)
Number of positions	25
Plug connector, control side	D-SUB connector (IEC 60807-2/DIN 41652)
Number of positions, control side	25
Number of connectors, control side	1
Plug connector, module side	D-SUB connector (IEC 60807-2/DIN 41652)
Number of positions, module side	25
Number of connectors, modul side	1
Fixed cable length	1 m
Single wire, cross section	0.25 mm ²
AWG	24
External diameter	10.5 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

Certificates / Approvals



Certification

CUL, UL

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;