

CABLE-FCN40/4X14/ 1,0M/S7-OUT


Order No.: 2321185



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2321185>

Assembled round cable for coupling 4x8 outputs of S7-300 card 6ES7 322-1BP50-0AA0. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK strips, length 1 m

Commercial data

GTIN (EAN)	 4 046356 331982
sales group	I680
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 233 (IF-2011)

Product notes

WEEE/RoHS-compliant since:
11/30/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Nominal voltage U_N	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A

Max. conductor resistance	0.16 Ω /m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Plug connector, control side	Fujitsu plug connector
Number of positions, control side	40
Number of connectors, control side	1
Plug connector, module side	Flat-ribbon cable strip (IEC 60603-1/DIN 41652)
Number of positions, module side	14
Number of connectors, modul side	4
Fixed cable length	1 m
Single wire, cross section	0.14 mm ²
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	6.3 mm
Shielding	no

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;