

FLK 50-PA/EZ-DR/KS/1100/YUC


Order No.: 2321389

Illustration shows the product FLK 50-PA/EZ-DR/KS/ 200/YUC



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2321389>

Assembled round cable with two molded 50-pos. socket strips (1:1 connection). Cable length: 11.0 m

Commercial data	
GTIN (EAN)	 4 046356 333030
Note	Made-to-order
sales group	I683
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 244 (IF-2011)

Product notes

WEEE/RoHS-compliant since:
12/10/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General	
Nominal voltage U_N	30 V DC
Max. current carrying capacity per path	500 mA (Up to 55°C ambient temperature)
Max. conductor resistance	0.16 Ω /m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Connector	Flat-ribbon cable connectors with insulation displacement connection method in acc. with DIN 41651
Number of positions	50
Number of positions, control side	50
Number of connectors, control side	1
Number of positions, module side	50
Number of connectors, modul side	1
Fixed cable length	11 m
Single wire, cross section	0.14 mm ²
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	11 mm

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;