


# CABLE-FCN40/4X14/ 1,0M/M340

Order No.: 2321729



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2321729>

Assembled round cable (40-pos. Fujitsu strip on four 14-pos. FLK strips) for coupling 32 channels to I/O cards of MODICON® M340 (BMX DDI 3202K, BMX DDI 6402K, BMX DD0 3202K, BMX DD0 6402K, BMX DDM 3202K); cable length 1 m

Commercial data	
GTIN (EAN)	 4 046356 412520
Note	Made-to-order
sales group	I680
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 227 (IF-2011)

### Product notes

WEEE/RoHS-compliant since:  
06/05/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

General	
Nominal voltage $U_N$	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A

Max. conductor resistance	0.16 Ω/m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Plug connector, control side	Fujitsu plug connector
Number of positions, control side	40
Number of connectors, control side	1
Plug connector, module side	Flat-ribbon cable strip (IEC 60603-1/DIN 41652)
Number of positions, module side	14
Number of connectors, modul side	4
Fixed cable length	1 m
Single wire, cross section	0.14 mm <sup>2</sup>
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	6.3 mm
Shielding	no

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;