


# EMD-SL-PS-230AC

Order No.: 2866129



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866129>

Power modules, pluggable, for EMD-SL-..., supply voltage: 195...264 V AC

Commercial data	
GTIN (EAN)	4 017918 952693 
sales group	H290
Pack	1 pcs.
Customs tariff	85043180
Catalog page information	Page 724 (IF-2011)

#### Product notes

WEEE/RoHS-compliant since:  
04/11/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>Input data</b>	
Nominal input voltage	230 V AC (50/60 Hz)
AC input voltage range	195 V AC ... 264 V AC
<b>General data</b>	
Width	32 mm

Height	35 mm
Depth	16 mm
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;