


# FL MEM PLUG

Order No.: 2891259



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2891259>

Exchangeable configuration memory of the device settings for simple device exchange and set-up

Commercial data	
GTIN (EAN)	 4 046356 165440
sales group	K000
Pack	1 pcs.
Customs tariff	84717098
Catalog page information	Page 103 (AX-2011)

### Product notes

WEEE/RoHS-compliant since:  
07/04/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Product description

Memory plug, configuration memory, replaceable

### Technical data

#### Function

Basic functions	Configuration memory (plug-in)
-----------------	--------------------------------

**General data**

Width	16 mm
Height	57 mm
Mounting type	In the host system
Type AX	Fine granularity
Weight	25 g
Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (no condensation)
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 95 % (no condensation)
Noise emission	EN 61000-6-3/-4
Noise immunity	EN 61000-6-2:2005

**Conformity with EMC directives**

Developed in acc. with standard	IEC 61000-6.2
Test standard	IEC 61000-4-2 (ESD)
Test result	Criterion B
Test standard	IEC 61000-4-3 (immunity to radiated interference)
Test result	Criterion A
Test standard	IEC 61000-4-4 (burst)
Test result	Criterion A
Test standard	IEC 61000-4-5 (surge)
Test result	Criterion A
Test standard	IEC 61000-4-6 (immunity to conducted interference)
Test result	Criterion A
Test standard	IEC 61000-4-8 (immunity to magnetic fields)
Test result	Criterion A
Test standard	EN 55022 (emitted interference)
Test result	Criterion A

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;