

TOE JACKS

Part Number	Capacity (tons)	Stroke (in)	Min. Height (in)	Max. Handle Effort (lbs.)	Weight (lbs.)
JT2-5	2	4.73	0.67	76.4	18
JT5-5	5	4.73	1.06	49.5	49
JT10-6	10	5.71	1.22	56.2	78



DESCRIPTION

- Low toe height to fit in tight spaces.
- 5T and 10T models with swivel sockets allow access in close quarters.
- Self contained for versatility.
- Low handle operation for ease of operation.
- For structural moving, rigging, machine lifting, forklift service and more.

BOTTLE JACKS

Part Number	Capacity (tons)	Stroke (in)	Min - Max Height (in)	Ext Screw Length (in)	Saddle Dia. (in)	Weight (lbs.)
JB5-5	5	4.66	7.88 - 15.25	2.75	1.13	7.9
JBL12-4	12	3.44	6.97 - 13.38	3.00	1.67	14
JB12-6	12	5.75	9.50 - 18.38	3.13	1.50	17
JBL20-4	20	3.31	7.22 - 12.00	1.50	2.06	22
JB20-7	20	6.22	10.67 - 16.88	-	2.38	27
JB30-7	30	6.25	11.06 - 17.31	-	2.41	40

DESCRIPTION

- Heavy steel construction, cylinder, oil reservoir and pump housing are welded to the hydraulic base.
- Chrome plated rod. Pump piston is heat treated & hard chrome plated.
- Equipped with an internal load limiting device. The automatic by-pass system prevents ram over-travel.
- Operates in vertical, angled, or horizontal position.
- Load tested to 150% capacity, easy to repair.

