

PERFORMANCE AND DURABILITYIN AC FUEL TRANSFER PUMPS



Ideal for fixed location, high volume fuel transfer, and a popular choice with Fuel Management Systems.

Manufactured from only the highest quality materials like cast iron, sintered bronze, and featuring Buna-N seals, these pumps provide exceptional durability for a wide variety of fuels. Explosion proof motors and UL listed models are your assurance of safety.

Additionally, a complete line of meters and accessories mean you can customize your fuel transfer system. From a simple mechanical meter, a hose, and a manual nozzle all the way up to a digital pulse output meter and ultra high flow automatic nozzle, nothing beats Fill-Rite® fuel transfer equipment.



FEATURES

- Cast Iron Construction
- 30 Minute Duty Cycle
- UL/cUL Certified Motor

- Gasoline, Diesel, B20, E-15, and Kerosene Compatible
- 2" NPT Bung Mount



FILL-RITE. AC FUEL TRANSFER PUMPS

	SD600 Series 13 GPM • 8' Lift • For use with Skid Tanks 115 Volt • Excellent choice for light duty applications		
SD602G	SD602G	FR610G	
Flow Rate (GPM/LPM)	Up to 13/49	Up to 15/57	
Inlet/Outlet	1"/3/4"	1"/3/4"	
Horse Power	1/6	1/6	
Hz	60	60	
Amps	1.5	1.5	
Included Accessories	Three Piece PVC Suction Pipe, 3⁄4" x 12' Hose, 3⁄4" Manual Nozzle	20 - 34 ¾" Steel Telescoping Suction Pipe, ¾" x 12' Hose, ¾" Manual Nozzle	



FR700 Series · Heavy Duty

For use with Above Ground and Underground Tanks

110	FR/UUV	FR/UTV	FR/UTVL	FR/TUVN	FR/TTVA
Flow Rate (GPM/LPM)	Up to 20/75	Up to 20/75	Up to 20/75	Up to 20/75	Up to 20/75
Inlet/Outlet	1 1/4" / 3/4"	11/4" / 3/4"	11/4" / 3/4"	11/4" / 1"	11/4" / 1"
Horse Power	1/3	1/3	1/3	1/3	1/3
Hz	60	60	60	60	60
Amps	5.5	5.5	5.5	5.5	5.5
Included Accessories	³ /4" x 12' Hose, ³ /4" Manual Nozzle (For Pump Only order FR700VN)	³ / ₄ " x 12' Hose, ³ / ₄ " Manual Nozzle, Mechanical Meter (Gal)	³ / ₄ " x 12' Hose, ³ / ₄ " Manual Nozzle, Mechanical Meter (Liter)	Pump Only	1" x 18' Hose, 1" Ultra Hi-Flow Auto Nozzle, Mechanical Meter (Gal)



FR300 Series · Heavy Duty

• Diesel and Gasoline • For use with Above Ground and Underground Tanks

18' Lift
 35% Faster Flow

115/230 Volt • For Large Fleets

The second secon	,					
R319VB 🎏 🔣	FR310VN	FR311VN	FR311VB	FR311VLB	FR319VB	
Flow Rate (GPM/LPM)	Up to 35/132	Up to 35/132	Up to 35/132	Up to 35/132	Up to 35/132	
Inlet/Outlet	11/4" / 1"	11/4" / 1"	11/4" / 1"	11/4" / 1"	11/4" / 1"	
Horse Power	3/4	3/4	3/4	3/4	3/4	
Hz	50/60	50/60	50/60	50/60	50/60	
Amps	9.8/4.9/11.4/5.7	9.8/4.9/11.4/5.7	9.8/4.9/11.4/5.7	9.8/4.9/11.4/5.7	9.8/4.9/11.4/5.7	
Included Accessories	Pump Only	Mechanical Meter [Gal]	1" x 18' Hose, 1" Ultra Hi-Flow Auto Nozzle, Mechanical Meter [Gal]	1" x 18' Hose, 1" Ultra Hi-Flow Auto Nozzle, Mechanical Meter (Liter)	1" x 18' Hose, 1" Ultra Hi-Flow Auto Nozzle, Digital Meter	

