

Valve Specifications

Operating Pressure (Air)

Maximum:

150 PSIG
200 PSIG for Model No. 0R37TB (PTFE diaphragm)

Minimum:

3 PSIG
50 PSIG for Model No. 0R37TB (PTFE diaphragm)

Operating Temperature:

Urethane: 0°F to 180°F* (-18°C to 80°C)
Nitrile: 0°F to 180°F* (-18°C to 80°C)
Fluorocarbon: 0°F to 400°F* (-18°C to 205°C)
PTFE: 0°F to 500°F* (-18°C to 260°C)

* Ambient temperatures below freezing require moisture-free air.
Ambient temperatures below freezing and above 180° require lubricants especially selected for suitability at these temperatures.
Pneumatic valves should be used with filtered and lubricated air.

Component Materials

Body Material..... Die cast aluminum

Static Seals.....Nitrile standard with urethane
(Others see below)

Diaphragm Standard – Urethane
Optional – Fluorocarbon, PTFE, or Nitrile
(Depending on size)

General Information


Quick exhaust valves provide rapid exhaust of control air when placed between control valve and actuator. They can also be used as shuttle valves. Diaphragm materials are available in urethane, Nitrile, Fluorocarbon, and PTFE to meet a wide variety of operating conditions.

Mounting Bracket Kit –

No. 03640 8100

(Including body screws)

For "0R12" and "0R25" sizes
with 7/8" "A" Dimension.



Model Selection, Performance Data and Dimensions

| Port | | | Flow (SCFM)† | Model Number | | A | B | C | Service Kit No. |
|---|------|------|--------------|----------------|----------|------------|------|------|-----------------|
| 1 | 2 | 3 | | NPTF | BSPP "G" | | | | |
| STANDARD URETHANE DIAPHRAGMS (Nitrile static seals) | | | | | | | | | |
| 1/4" | 1/4" | 3/8" | 150 | 0R25NB | 0RB25NB | 1" Hex | 2.06 | 2.44 | 03340 0105 |
| | 3/8" | 3/8" | 240 | 0R25PB | — | 1" Hex | 2.06 | 2.44 | 03340 0105 |
| 3/8" | 3/8" | 3/8" | 240 | 0R37B | 0RB37B | 1" Hex | 2.06 | 2.44 | 03340 0105 |
| 1/2" | 1/2" | 1/2" | 450 | 0R50B | 0RB50B | 1-1/2" Hex | 2.88 | 3.38 | 03475 0109 |
| 3/4" | 3/4" | 3/4" | 550 | 0R75B | 0RB75B | 1-1/2" Hex | 2.88 | 3.38 | 03475 0109 |
| NITRILE DIAPHRAGMS (Nitrile static seals) | | | | | | | | | |
| 1/8" | 1/8" | 1/8" | 70 | 0R12B | 0RB12B | 7/8" Sq. | 1.75 | 1.88 | 03640 8000 |
| | 1/8" | 1/4" | 70 | 0R12NB | 0RB12NB | 7/8" Sq. | 1.75 | 1.88 | 03640 8000 |
| 1/4" | 1/4" | 1/4" | 90 | 0R25B | 0RB25B | 7/8" Sq. | 1.75 | 1.88 | 03640 8000 |
| | 1/4" | 3/8" | 90 | 0R25NFB | 0RB25NFB | 7/8" Sq. | 1.75 | 1.88 | 03340 8000 |
| 3/8" | 3/8" | 3/8" | 240 | 0R37FB | 0RB37FB | 1" Hex | 2.06 | 2.44 | 03340 8000 |
| 3/4" | 3/4" | 3/4" | 550 | 0R75FB | 0RB75FB | 1-1/2" Hex | 2.88 | 3.38 | 03475 9000 |
| FLUOROCARBON DIAPHRAGMS for extended temperature operation (Fluorocarbon static seals) | | | | | | | | | |
| 1/8" | 1/8" | 1/8" | 70 | 0R12VB | 0RB12VB | 7/8" Sq. | 1.75 | 1.88 | 03650 8000 |
| | 1/8" | 1/4" | 70 | 0R12NVB | 0RB12NVB | 7/8" Sq. | 1.75 | 1.88 | 03650 8000 |
| 1/4" | 1/4" | 1/4" | 90 | 0R25VB | 0RB25VB | 7/8" Sq. | 1.75 | 1.88 | 03650 8000 |
| 3/8" | 3/8" | 3/8" | 240 | 0R37VB | 0RB37VB | 1" Hex | 2.06 | 2.44 | 03340 0319 |
| 1/2" | 1/2" | 1/2" | 450 | 0R50VB | 0RB50VB | 1-1/2" Hex | 2.88 | 3.38 | 03475 0120 |
| 3/4" | 3/4" | 3/4" | 550 | 0R75VB | 0RB75VB | 1-1/2" Hex | 2.88 | 3.38 | 03475 0120 |
| PTFE DIAPHRAGMS for higher pressure and temperature (Fibre static seals) | | | | | | | | | |
| 3/8" | 3/8" | 3/8" | 240 | 0R37TB | 0RB37TB | 1" Hex | 2.06 | 2.44 | 03340 0504 |

† At 100 PSIG inlet pressure with full pressure drop.

BOLD ITEMS ARE MOST POPULAR.

